Section Number	Title
12 20 00	WINDOW TREATMENTS
12 21 00	Window Blinds
12 24 00	Window Shades
12 24 13	Roller Window Shades
12 50 00	FURNITURE
12 51 00	Office Furniture
12 51 16	Case Goods
12 51 19	Filing Cabinets
12 51 16.1	6 Wood Case Goods
12 51 16.19	9 Plastic Laminate Case Goods
12 51 23	Office Tables
12 52 00	Seating
12 56 00	Institutional Furniture
12 56 33	Classroom Furniture
12 56 39	Lecterns
12 56 52	Audio-Visual Furniture
12 59 00	Systems Furniture
12 59 16	Free-standing component Systems Furniture
12 59 13	Panel-Hung component Systems Furniture
12 60 00	MULTIPLE SEATING
12 61 00	Fixed Audience Seating
12 90 00	OTHER FURNISHINGS
12 93 00	Interior Public Space Furnishings

Trash and Litter Receptors

12 93 23

Section Number Title

### 12 20 00 WINDOW TREATMENTS

#### Part 1 - General

If easily accessible, window coverings can be manually operable; otherwise, coverings must be motorized with controls located at the instructor's workstation on the AV touch panel. Where applicable, the depth of the window shall be designed to allow for the installation of motorized shade tracks.

Vertical blinds and drapes are not desired. If necessary, they are to have non-plastic, heavy-duty operating components.

All window treatments are required to have a non-reflective matte finish and unless otherwise specified, the color selection shall match or blend with the window frame.

Part 2 - Products

N/A

Part 3 - Execution

N/A

#### 12 21 00 Window Blinds

Part 1 - General

Horizontal blinds are permitted, pending submittal review and approval by Owner.

Part 2 – Products

N/A

Part 3 - Execution

N/A

#### 12 24 00 Window Shades

12 24 13 Roller Window Shades

Part 1 - General

Use of a light diffusing and room darkening (where applicable) roller shades are preferred. DP shall calculate percentages of light diffusion for each window by evaluating the individual window's orientation and the intensity of the exposure.

Part 2 – Products

N/A

Part 3 - Execution

N/A

#### 12 50 00 FURNITURE

#### Part 1 - General

Furniture selection is dictated by NAU standards for classrooms and office spaces in the Design Guidelines. Owner will procure furniture, unless otherwise identified. All final furniture selections will be reviewed and approved by Owner prior to order placement. All furniture drawings shall be reviewed for code compliance prior to final specification. For additional information refer to the Design Guidelines.

Owner will assist the Design Professional with the selection of products based on their requirements. Drawings, furniture plans and electrical plans, and furniture specifications are to be provided to Owner for review and final approval. The furniture specifications are to be provided with the information per item listed here.

Item No./Callout indicated on spec sheet and furniture plans

Manufacturer indicate style/series, Manufacturer Number,

Dimensions and Description; provide photo of item indicate manufacturer, pattern, color, width,

repeat, application, and use of multiple fabric;

provide photo image of fabric

Finishes indicate color and application: provide photo image

of finish

Notes as needed for further information to order the

furniture accurately

Room # & Location

Quantity

Fabric

Part 2 - Products

N/A

Part 3 - Execution

N/A

12 51 00 Office Furniture

12 51 16 Case Goods

Part 1 - General

N/A

#### Part 2 – Products

# **Open Office Furniture**

Integrated options to be available in selected system

- a. Height Adjustment Adjustable worksurfaces from 24 ½" to 52" height
- b. Edge Detail 3MM plastic edge, bullnose or sloped edge; no laminate self edge
- c. Cable Routing Cable management system integral to the product
- d. Privacy Privacy screens and modesty panels required
- e. Worksurfaces Rectangular and curvilinear required
- f. Storage Pedestal storage to include box and file drawers with mobile option
- g. Storage Vertical Cabinets stand-alone & over desk storage open or closed (desk mounted)
- h. Worksurface Laminate covered particle board or steel core
- i. Cord Cutouts or Grommets shall be available on all worksurfaces
- j. Levelers Leveling glides required on all support legs with minimum ½" adjustment
- k. Size Minimum requirement depth desk unit 24" to 36"
- I. Size Minimum requirement width desk 30" to 72"

### Part 3 - Execution

N/A

### 12 51 16.16 Wood Case Goods

Part 1 - General

N/A

#### Part 2 – Products

Integrated options to be available in selected case good

- a. Desk
- a. Return
- b. Credenza
- c. Bridge
- d. Bullet table
- e. Lateral file
- f. Bookcase
- g. Service module

# **Specifications**

- a. Full height back panel and pedestals
- b. Wood drawer interior
- c. One hanging file folder frame per drawer
- d. Leveling glides
- e. Pencil tray

### Part 3 - Execution

N/A

## 12 51 16.19 Plastic Laminate Case Goods

# Part 1 - General

N/A

# Part 2 - Products

Integrated options to be available in selected case good

- a. Desk
- b. Return
- c. Credenza
- d. Bridge
- e. Bullet table
- f. Lateral file
- g. Bookcase
- h. Service module

## Specifications

- a. Full height back panel and pedestals
- b. Wood drawer interior
- c. One hanging file folder frame per drawer
- d. Leveling glides
- e. Pencil tray

# Part 3 - Execution

N/A

# 12 51 19 Filing Cabinets

# Part 1 - General

N/A

# Part 2 - Products

Integrated options to be available in selected storage LATERAL FILES

- a. Steel construction
- b. Available Front to back or side to side drawer configuration
- c. Locking
- d. Available Multiple widths (30",36" & 42")
- e. Available in multiple heights (26 1/4" to 62 3/4")(minimum)
- f. Leveling glides
- g. Laminate top option
- h. Safety interlock to open one (1) drawer at a time
- i. Counterweights (required)

### **BOOKCASES**

- a. Steel construction
- b. Available Multiple widths (30",36" & 42")
- c. Available in multiple heights (26" to 65")(minimum)
- d. Adjustable shelves
- e. Laminate top option

## STORAGE CABINETS

- a. Steel construction
- b. Adjustable shelves
- c. Locking
- d. Available in multiple heights 26" to 65" minimum
- e. Available in Multiple widths
- f. Available in 18" depth (minimum)

### Part 3 - Execution

N/A

#### 12 51 23 Office Tables

# Part 1 - General

N/A

### Part 2 - Products

Integrated options to be available in selected table style

- a. Round Top diameters (30" to 60")(minimum)
- b. Square Top dimensions (30"X30") to (48"X48") (minimum)
- c. Rectangular Top dimensions (24"X48") to (30"X72")(minimum)
- d. Laminate Top
- e. Leveling Glides
- f. Chrome Base Option
- g. Caster option for smaller tables

#### Part 3 - Execution

N/A

# 12 52 00 Seating

Part 1 - General

N/A

# Part 2 - Products

# **High Performance Ergonomic Task Seating**

Integrated options to be available in selected chair style

- a. Adjustable seat angle
- b. Adjustable back angle, tilt and vertical adjustment
- c. Adjustable seat depth and tilt
- d. Adjustable back height
- e. Pneumatic height adjustment
- f. Swivel tilt
- g. Height, width and pivot adjustable arms
- h. Armless
- i. Soft arm caps
- j. Fully upholstered back panel
- k. Available with high and mid back
- I. Available in Plus and Small size frames
- m. Five arm base w/dual wheel casters
- n. Soft and hard wheel casters

### **Side Seating**

Integrated options to be available in selected chair style

- a. Sled base
- b. Leg base with hard and soft caster option
- c. Plastic or poly seat and back
- d. Upholstered seat and back
- e. Plastic arm caps
- f. Frame colors available
- g. Chrome frame available
- h. Standard back height

# **Conference seating**

Integrated options to be available in selected chair style

- a. Five arm base with casters
- b. Leg base with caster option
- c. Fixed arms
- d. Pneumatic height adjustment
- e. Tilt lock
- f. Soft arm caps

Part 3 - Execution

N/A

### 12 56 00 Institutional Furniture

12 56 33 Classroom Furniture

Refer to Design Guidelines.

12 56 39 Lecterns

**Instructor Station** 

Refer to Design Guidelines.

12 56 52 Audio-Visual Furniture

Refer to Design Guidelines.

# 12 59 00 Systems Furniture

12 59 13 Panel-Hung component Systems Furniture

### Part 1 - General

Integrated options to be available in selected system

- a. Compliance with ANSI/BIFMA X5.6-2003 for all panels, components, wiring & lighting.
- b. The Entire System shall be U.L. approved.
- c. The complete system shall be of one (1) product manufacturer.
- d. Panel Types
  - i. fabric covered acoustical panel
  - ii. glazed panel
  - iii. door panel
  - iv. pass through panel
  - v. tackable acoustical panel
- e. Panel Size fabric covered shall be available in six panel heights ranging from 30'' to 80'' and at least six (6) panel widths ranging from 18'' to 60''. Panels shall be a minimum of  $2 \frac{1}{2}$  thick.
- f. Configuration of Panels Panels shall be fully interchangeable between various sizes and heights and shall be capable of being arranged in a variety of configurations having two, three and four panels radiating from a single source
- g. Attachment to Walls Panels shall have provisions for attachment to permanent walls when required.
- h. Panels shall have 1" incremental hanging capability for worksurfaces, bins and shelves inherent in the panel frame for the full height of the panel.
- i. Cover Material Fabric covered panels shall be covered on front and back.

- The fabric shall be of a woven texture; colors shall be available in muted tones (preferably grays, beige etc.)
- j. Installation/Reconfiguration Panel systems shall be capable of being moved and reinstalled easily without the use of highly specialized tools.
- k. Cleaning All surfaces of the system shall resist stain and be easily cleaned
- Modification The system shall be capable of adding electrification components in the field at some future time with a minimum of panel modification.
- m. Finish Detail The system shall be void of sharp-edged components
- n. Core Construction Core construction shall allow panel to be rigid and capable of supporting loaded components. Core construction shall not allow for flexing or torqueing of panel. Panel system strength should be strong without the use of floor supported products (peds, end panels, lateral files, etc.). Counterbalance of system components should not be required.
- o. Sound Resistance Acoustical panels shall have a minimum of .80 NCR sound classification as tested in accordance with ASTM, C-423-90a and a minimum STC of 20 as tested in accordance with ASTM, e-413-87 (1994) shall be available within the product line. Tackable acoustical panels shall have a minimum of .65NRC sound classification as tested in accordance with the above standards.
- p. Fire Resistance All panels shall have Class A fire rating as tested in accordance with ASTM, E84-96a.
- q. Connectors Panel connectors shall be re-usable where necessary to connect adjacent panels to form the panel structure. Panel connectors shall be made of strong materials. The system shall have simple rigid connections.
- r. Edges & Fillers All panel edges not joined to another panel shall be provided with a finished end cap. Corner fillers shall be used at all junctions between panels.
- s. Trim All vertical trim shall be of metal frame and painted. Vertical side frames shall have concealed painted inserts slotted up to 1 ½" centers to maximize vertical utilization of components. The panel top shall be trimmed with a vinyl; steel, wood or fabric-covered extrusion cap and shall match the system color scheme.
- t. Levelers A minimum of two (2) panel supported levelers shall be used to provide a rigid panel system and shall have the capability top level panels on an uneven floor. Levelers shall support the weight of the system. Levelers shall have a minimum vertical adjustment of  $\frac{1}{2}$ ".
- u. Raceways Raceways shall be at the top and the bottom of panels. Raceways shall be either integral or capable of being integrated into panels. Cabling within the raceway shall be concealed at all junctions between panels. Raceways shall make provisions for distribution of electrical wiring to run adjacent to data and telephone cabling. Electrical wiring shall be

- mechanically isolated if not shielded or in conduit.
- v. Electrical Requirements The minimum electrical requirement shall be for a 4-circuit 8-wire system. Panels with raceways that are 24" or wider, shall have a minimum of two (2) receptacles per side and have space available for an additional port for installation of data and telephone receptacles. Electrical systems offered shall be 102v, 20-amp circuits capable of transitioning through multiple panel intersections. All receptacles whether simplex or duplex, shall support a minimum of 15 amps electrical load.
- w. Power Poles Power poles shall be available and shall be capable of attaching to the top or the end of a panel. Or to a connecting junction and integrating with the panel electrical system.
- x. Required Components
  - Task Lighting LED type, U.L listed and conforms to the National Electric Code
  - ii. Work Surfaces Shall be either steel or particle board covered with laminate. Particle board to have backer sheet underside. Minimum thickness to be 1 ¼" thick. All exposed edges shall be finished to match the worksurface or have a vinyl edge band
  - iii. Work surfaces to be cantilever or floor supported
  - iv. Cord Cutouts or Grommets shall be available on all worksurfaces
  - v. Storage Drawers required to include file drawers, box drawers, pencil drawers, pedestals, and flipper door storage cabinets.
  - vi. Security All storage with the exception of the pencil drawer shall have the capability of being locked.

## Part 2 – Products

N/A

### Part 3 - Execution

N/A

### 12 59 16 Free-standing component Systems Furniture

#### Part 1 - General

Integrated options to be available in selected system

- a. Height Adjustment Adjustable worksurfaces from 24 ½" to 52" height
- b. Edge Detail Bullnose, sloped edge, 3mm edge
- c. Cable Routing Cable management system integral to the product
- d. Privacy Privacy screens and modesty panels required
- e. Worksurfaces Rectangular and curvilinear required

- f. Storage Pedestal storage to include box and file drawers with mobile option
- g. Storage Lateral File, counterweights must be included
- h. Storage Vertical Cabinets standalone & over desk storage open or closed (desk mounted)
- i. Worksurface Laminate covered particle board or steel core
- j. Counter Tops Transaction Worksurfaces
- k. Spanner Tables Worksurfaces to connect workstations
- I. Jetty Tables/Peninsula Tables
- m. Cord Cutouts or Grommets shall be available on all worksurfaces
- n. Levelers Leveling glides required on all support legs with minimum ½" adjustment
- o. Column mounted Shelves and Screens
- p. Multiple screen heights for privacy
- q. Multiple worksurface offerings for corner and straight units.
- r. Desk Size Minimum requirement depth desk unit 24" to 30"
- s. Desk Size Minimum requirement width desk 24" to 78"
- t. Corner Unit Size
- u. Storage Towers
- y. Required Components
  - Task Lighting LED type, U.L listed and conforms to the National Electric Code
  - ii. Work Surfaces Shall be either steel or particle board covered with laminate. Particle board to have backer sheet underside. Minimum thickness to be 1 ¼" thick. All exposed edges shall be finished to match the work surface or have a vinyl edge band
  - iii. Work surfaces to be cantilever or floor supported
  - iv. Cord Cutouts or Grommets shall be available on all work surfaces
  - v. Storage Drawers required to include file drawers, box drawers, pencil drawers, pedestals, and flipper door storage cabinets.
  - vi. Security All storage except for the pencil drawer shall have the capability of being locked

Part 2 – Products

N/A

Part 3 - Execution

N/A

#### 12 60 00 MULTIPLE SEATING

# 12 61 00 Fixed Audience Seating

Refer to Design Guidelines.

Contractor shall submit shop drawings for review and approval by Owner.

#### 12 90 00 OTHER FURNISHINGS

## 12 93 00 Interior Public Space Furnishings

12 93 23 Trash and Litter Receptors

# **Lobby Unit Recycling and Trash Standards**

These standards are intended to create a unified and consistent recycling and landfill waste system on campus. <u>All final designs must be approved by Owner</u> (Office of Sustainability).

#### **Colors:**

- Blue for recycling and Brown for waste.
- Lettering and symbols should be white.
- All panels of the bin should be appropriately colored.

Wording: "Landfill" for waste and "Recycling" for recyclables.

#### Symbols:

- The white universal recycling symbol is to be used for recycling and the white "waste person" symbol is to be used for "Landfill".
- There will be a symbol on the top, front and both sides of the bin, excluding the back.

#### **Shape of Unit:**

- Unit is to be rectangular in shape and "Landfill" and "Recycling" sections should be connected so that the unit is one dual unit.
- Left side is "Landfill" and right is "Recycling."
- The unit will be front loading with rectangular openings.
- Unit HxWxD should not exceed 46"x43"x21".

### Liners, Capacity, & Other:

- Each side will have approximately 32 gallons of capacity.
- Liners will accommodate a 38x58 flat cut bag.
- Front of unit will open on each side to give access for servicing.
- Units must be constructed with a majority of post-consumer recycled content.

Max-R.

As an example, previous manufacturers that have been used were Clean River and

<u>All final designs must be approved by Owner (Office of Sustainability).</u> This is an Owner furnished item.



Small and Medium Bins

For other areas that do not require the capacity of a lobby unit small and medium recycling and waste bins should be used. As for the lobby units recycling with be blue with a white recycling symbol and waste will be brown with the white "waste person" symbol. This is an Owner furnished item. All final designs must be approved by the Owner (Office of Sustainability).

Examples of bins that meet these requirements are:

**Medium Recycling:** Tough Guy Recycling Container, 23 gal, Blue Manufacturer Number 4UAU7

**Medium Waste:** Tough Guy Open-Top Trash Can, Rectangular, 23 gal Manufacturer Number 10F624

Section Number Title

**Small Recycling:** Rubbermaid Recycling Container, 7 gal, Blue, Manufacturer Number FG295673

**Small Waste:** Continental rectangular wastebasket, 7 gal, Brown Manufacturer Number 2818BN



\*\*END OF SECTION\*\*